

This manual describes how to configure your tool with P&A code to enable WIFI updates

Step 1: Go to settings -> Info -> Factory reset

_	Version Info	ormation 🔶 🛜
	Serial Number	2524206789
¢.	Wi-Fi MAC Address	6c:c3:74:f2:05:ed
	Configuration Version	192-411987-H00-0011
	Data Version	192-481986-A01-0028
_	Controller Version	192-471989-H00-0011
-1	Diagnostic Conce Version	192-221974H-8.05
		YOU ONG 4 4 2 DE\/D16 120220
i	(IJ	© LI

Step 2: Confirm factory settings

	ft 👘				Ŷ
-	Serial N	umber	2524206789		
¢.	Wi-Fi M		Warning	ed	
	Configu	Are you sure	you want to return to	0-0011	
	Data Ve	factory settings?		28	
	Control			0-0011	
	Diagno	No	Yes	.05	
-	OS Vorci				20220
0	(!)			©	(†)

Step 3: Warning: Your tool will clear all history records and user settings



Step 4: Configure language settings and press next

Language Settings			N.	
System Language			English (US)	•
Test Result Language			English (US)	•
Email Language			English (US)	•
Print Language			English (US)	•
				lext

Step 5: Ford dealer, select 'Yes'

Ford Selection	- AN
Are you a Ford dealership? No Yes	
Back	

Step 6: Enter your name / ID

		Create User	ð.	2
	WSLX ID: _		Next	
Back				

P&A setup

Step 7: Select date/time settings and press next

Date/Tir	ne Settings 🛛 🕅 🕅
Select Time Format	24 Hour 👻
Select Date Format	13/02/2024 (DD/MM/ 🖌 YYYY)
Select Time Zone	Central Time 🔻
Set Date	
Back	Next

Step 8: Select test settings and press next

Test Setting	ys 🕅 🕅
Temperature Units	° F 🕶
Decimal Separator	00.00 -
Buzzer	
Back	Next

Step 9: Search and configure active WIFI network

Add Wi-Fi Network			N.	1.
>Mikrotik	÷	ŝ	>	
Accu Diagnose	÷	ŝ	>	
DEV Test	÷	ŝ	>	
MidWiFi-GUEST		ŝ	>	
bvGuest	÷	î	>	
+		×	(



Step 10: Location selection, enter 65099



Step 11: Select location



Step 12: Verify location



P&A setup

Step 13: Confirm location



Step 14: Login and confirm safety warning

Step 15: Go to settings ->	Info -> Check	for updates
----------------------------	---------------	-------------

1	Version Info	ormation	Ŷ
	Serial Number	1119112345	
\$	Wi-Fi MAC Address	34:15:13:33:f8:b1	
	Configuration Version	192-411987-C00-0006	
	Data Version	192-481986-A01-0013	
_	Controller Version	192-471989-C00-0006	
	Diagnostic Device Version	192-221974B-2.19	
	OS Varsian	YOU ON # 4 4 7 DE\/016	20
(j)	(IJ	©	(†)

Step 16: If conditions are correct, update should be found as shown below. Press Yes to start update. Please make sure to connect your IMI-2404.



Step 17: Update will start and will take approximately 5 - 15 minutes



